

Product Information

General Specifications



spectrum+ max provides a heavy duty defence against deterioration for locations with high corrosion risk such as coastal and seaside environments. With an extensive choice of play activities and colour options, it combines durability and high visual impact.

MAIN UPRIGHTS

75 x 75mm aluminium with powder coat finish.

PLATFORM DECKS

Aluminium sheet with punched dimple pattern and slip resistant powder coat.

ROOFS

Primed and powder coated pre-galvanised sheet steel, corrugated steel sheeting or rotomoulded plastic as specified.

SAFETY RAILING

900mm high guardrail panels on platforms over 500mm.

Primed and powder coated pre-galvanised steel tube or HDPE plastic panels as specified.

HANDGRIPS

27mm O/D pre-galvanised steel tube with primed and powder coated finish.

Supplied at climbing access points as appropriate.

Access ladders include 27mm O/D handgrip integrated in ladder side.

HANDRAILS

34mm O/D galvanised steel tube with primed and powder coated finish.

PLAY COMPONENTS

Fabricated from pre-galvanised steel, welds treated with zinc rich primer – primed and powder coated finish.

SLIDES

Heavy duty reinforced fibreglass, rotomoulded plastic or stainless steel as specified.

TUNNELS

Primed and powder coated galvanised steel tube with end panels.

ACTIVITY PANELS

Rotomoulded plastic beads or HDPE plastic sheet panels as appropriate.

CLIMBING ROPES

Synthetic strands braided over a galvanised steel wire core.

HARDWARE

Vandal resistant 316 stainless steel fasteners.

FOOTINGS

Concrete to a minimum depth of 500mm with earth hard packed to mouth of hole.

POWDER COAT PRIMER LAYER

A zinc rich powder coat primer base layer is applied to all galvanised steel components.