


 Made in Australia



- Provide undersurfacing in accordance with AS 4422 (Int.):2022. Mulch undersurfacing should be 200mm minimum compacted depth.
- Plans and illustrations are schematic only, actual details may vary. Do not scale for dimensions. Allow 5% minimum additional clearance for site variations.

• FHOF - Free Height Of Fall as per AS 4685:2021

• GC - Ground Clearance under swing attachments used to calculate impact area, free space and FHOF

• Falling Space:



## Materials

### Main Uprights

- Galvanised Steel
- Aluminium
- N/A

### Platforms

- Galvanised Steel
- White Cypress Timber
- Aluminium
- N/A

### Shop Counter

- HDPE
- White Cypress Timber
- Composite
- N/A

### Wall Climber/Rock Wall /Scaling Wall

- HDPE
- White Cypress Timber
- N/A

### Corrosion Protection

- Zinc Primed Welds
- Full Zinc Primer Coat

### Fasteners

- Class 3/Galvanised
- Stainless Steel

### Guardrails

- Steel Pipe
- Plastic Panels
- Plastic Slat
- White Cypress Timber
- Perforated
- Composite
- Paling
- Custom
- N/A

## Colours

### Powder Coat

Berry Grey  
Intensity Summer

### Corrugated Sheet

N/A

### Timber

N/A

## HDPE Plastic

Blue/Yellow/Blue

## Wire Rope

N/A

## Rotomoulded Plastic

N/A