



- Provide undersurfacing in accordance with AS 4422 (Int.):2022. Mulch undersurfacing should be 200mm minimum compacted depth.
- Plans and illustrations are schematic only, actual details may vary. Do not scale for dimensions. Allow 5% minimum additional clearance for site variations.

• FHOF - Free Height Of Fall as per AS 4685:2021

• GC - Ground Clearance under swing attachments used to calculate impact area, free space and FHOF

• Falling Space:



Materials

Main Uprights

- Galvanised Steel
- Aluminium
- N/A

Platforms

- Galvanised Steel
- White Cypress Timber
- Aluminium
- N/A

Shop Counter

- HDPE
- White Cypress Timber
- Composite
- N/A

Wall Climber/Rock Wall /Scaling Wall

- HDPE
- White Cypress Timber
- N/A

Corrosion Protection

- Zinc Primed Welds
- Full Zinc Primer Coat

Fasteners

- Class 3/Galvanised
- Stainless Steel

Guardrails

- Steel Pipe
- Plastic Panels
- Plastic Slat
- White Cypress Timber
- Perforated
- Composite
- Paling
- Custom
- N/A

Colours

Powder Coat

- Intensity Flame
- Intensity Moonlight

Corrugated Sheet

N/A

Timber

N/A

HDPE Plastic

Blue/Yellow/Blue

Wire Rope

N/A

Rotomoulded Plastic

N/A