


 Made in Australia



- Provide undersurfacing in accordance with AS 4422 (Int.):2022. Mulch undersurfacing should be 200mm minimum compacted depth.
- Plans and illustrations are schematic only, actual details may vary. Do not scale for dimensions. Allow 5% minimum additional clearance for site variations.
- FHOF - Free Height Of Fall as per AS 4685:2021
- GC - Ground Clearance under swing attachments used to calculate impact area, free space and FHOF
- Falling Space:
  - Minimum impact area as per AS 4685:2021
  - Required free space as per AS 4685:2021
  - Recommended clearance area
  - Circulation space as per AS 4685:2021

### Materials

#### Main Uprights

- Galvanised Steel
- Aluminium
- N/A

#### Platforms

- Galvanised Steel
- White Cypress Timber
- Aluminium
- N/A

#### Shop Counter

- HDPE
- White Cypress Timber
- Composite
- N/A

#### Wall Climber/Rock Wall /Scaling Wall

- HDPE
- White Cypress Timber
- N/A

#### Corrosion Protection

- Zinc Primed Welds
- Full Zinc Primer Coat

#### Fasteners

- Class 3/Galvanised
- Stainless Steel

#### Guardrails

- Steel Pipe
- Plastic Panels
- Plastic Slat
- White Cypress Timber
- Perforated
- Composite
- Paling
- Custom
- N/A

#### Colours

- Powder Coat**
- Intensity Juicy Lime
  - Intensity Summer
  - Dark Violet

- Corrugated Sheet**
- N/A

- Timber**
- N/A

- HDPE Plastic**
- N/A

- Wire Rope**
- N/A

- Rotomoulded Plastic**
- N/A