


Impact Area Cannot Be Overlapped By Another Impact Area



- Provide undersurfacing in accordance with AS 4422 (Int.):2022. Mulch undersurfacing should be 200mm minimum compacted depth.
- Plans and illustrations are schematic only, actual details may vary. Do not scale for dimensions. Allow 5% minimum additional clearance for site variations.
- FHOF - Free Height Of Fall as per AS 4685:2021
- GC - Ground Clearance under swing attachments used to calculate impact area, free space and FHOF
- Falling Space:
 - Minimum impact area as per AS 4685:2021
 - Required free space as per AS 4685:2021
 - Recommended clearance area
 - Circulation space as per AS 4685:2021

Note: This Swing Frame Is Suitable For Supervised Early Childhood Settings Only



Swing Attachments Illustrative Only

Made in Australia

Materials

Main Uprights

- 75 x 75 Galvanised Steel
- 75 x 75 Aluminium
- ⊗ 100 x 100 Galvanised Steel - Not Available
- ⊗ 125 x 125 White Cypress Timber - Not Available
- ⊗ 200 x 200 White Cypress Timber - Not Available

Fasteners

- Class 3/Galvanised
- Stainless Steel

Corrosion Protection

- Zinc Primed Welds
- Full Zinc Primer Coat

Colours

Powder Coat
Terrain
Wedgewood
Pale Eucalypt

Timber
N/A