



- Provide undersurfacing in accordance with AS 4422 (Int.):2022. Mulch undersurfacing should be 200mm minimum compacted depth.
- Plans and illustrations are schematic only, actual details may vary. Do not scale for dimensions. Allow 5% minimum additional clearance for site variations.
- FHOF - Free Height Of Fall as per AS 4685:2021
- GC - Ground Clearance under swing attachments used to calculate impact area, free space and FHOF
- Falling Space:
  - Minimum impact area as per AS 4685:2021
  - Required free space as per AS 4685:2021
  - Recommended clearance area
  - Circulation space as per AS 4685:2021



Swing Attachments Illustrative Only

Made in Australia

Plan and Concept © Adventure Playgrounds Pty. Ltd. 2024. Illustrations are for illustrative purposes only. Actual details may vary.

### Materials

#### Main Uprights

- ⊗ 75 x 75 Galvanised Steel - Not Available
- ⊗ 75 x 75 Aluminium - Not Available
- ⊗ 100 x 100 Galvanised Steel - Not Available
- ⊗ 125 x 125 White Cypress Timber - Not Available
- 200 x 200 White Cypress Timber

### Fasteners

- Class 3/Galvanised
- Stainless Steel

### Corrosion Protection

- Zinc Primed Welds
- Full Zinc Primer Coat

### Colours

**Powder Coat**  
N/A

**Timber**  
Old Gold